## Geckolighting® 10w LED Adjustable Downlight



## Geckolighting® LED 10w Adjustable Downlight.

Complete LED downlight unit with fully adjustable fitting for precise light placement. These high power LED downlights are ideal replacement units for halogen and R8o downlights. complete with dedicated LED driver.

Colour options of; Cool white - 6000K Warm white - 3000K



Input Voltage # Frequency Range   5	10W AC85-265V 50/60Hz 1000Im >0.96 Dimmable driver Epistar COB LED
Frequency Range 5 Initial luminous flux: 1 Power Factor(PF) 5 Driver: 5	50/60Hz 1000lm >0.96 Dimmable driver Epistar COB LED
Initial luminous flux: 1 Power Factor(PF) > Driver: 0	1000lm >0.96 Dimmable driver Epistar COB LED
Power Factor(PF) > Driver:	>0.96 Dimmable driver Epistar COB LED
Driver:	Dimmable driver Epistar COB LED
	Epistar COB LED
	•
LED source:	
Luminous efficiency:	>100lm/w
Light efficiency:	>90%
Operating temperature:	-30°C ~ +55°C
	CW - Cool white: 6,000K WW - Warm white: 3,000K
Color Index(CRI)	Ra>80
Beam Angle: 1	100°
Light Body& Lampshade	Aluminum Alloy and PC lens
Working Life 5	50,000 Hrs
IP Rating:	IP40
Cutout size:	110mm
Dimensions:	Diameter: 125mm x height: 90mm
Net Weight	0.2Kg





Geckolighting Phone: (08) 9248 6205 Fax: (08) 9248 3501 sales@geckolighting.com.au







